



US005968212A

United States Patent [19]

[11] Patent Number: 5,968,212

Peise et al.

[45] Date of Patent: Oct. 19, 1999

[54] APPARATUS FOR GASIFICATION OF
COMBUSTION AND WASTE MATERIALS
CONTAINING CARBON AND ASH

4,343,626 8/1982 Peise et al. 48/67
5,248,316 9/1993 Peise et al. 48/76

[75] Inventors: Helmut Peise; Manfred Schingnitz;
Dietmar Degenkolb, all of Freiberg,
Germany

FOREIGN PATENT DOCUMENTS

226 588 8/1985 Germany
394 299 9/1931 United Kingdom

[73] Assignee: Noell-KRC Energie-und
Umwelttechnik GmbH, Schkeuditz,
Germany

Primary Examiner—Hien Tran
Assistant Examiner—James Kennedy
Attorney, Agent, or Firm—Cohen, Pontani, Lieberman &
Pavane

[21] Appl. No.: 08/954,361

[22] Filed: Oct. 20, 1997

[30] Foreign Application Priority Data

Oct. 19, 1996 [DE] Germany 196 43 258

[51] Int. Cl.⁶ F16H 21/40; C10J 1/28;
C07C 1/00

[52] U.S. Cl. 48/101; 48/74; 48/123;
48/197 R; 110/346; 585/240; 422/139

[58] Field of Search 422/202, 139;
48/67, 74, 89, 94, 95, 99, 101, 123, 197 R;
585/240; 110/346

[56] References Cited

U.S. PATENT DOCUMENTS

4,188,915 2/1980 Kummel et al. 122/6 A

[57] ABSTRACT

A device for utilizing combustion, residual and waste materials containing carbon and ash by gasification with an oxygen-containing oxidizing agent at temperatures above the melting point of the inorganic parts in a reaction chamber and at a pressure between ambient pressure and 60 bar. The reaction chamber contour is formed in part by a refractory-grade lining and in part by a cooling system comprising cooling coils connected in a gas-tight manner. The coils are coated with a thin layer of a ceramic mass that conducts heat well on a side facing the reaction chamber. The cooling coils are operated, while being cooled by pressurized water, below or above the boiling point of the cooling water.

7 Claims, 3 Drawing Sheets

